

Product specification

1		Pfeifer Cable Tension Member type UMIX
1.1	1,00 pc	<p>Pfeifer cable tension member type UMIX consisting of: 1 pc. open swaged fitting type 620, 1 pc. open swaged fitting with turnbuckle type 624, 1 pc. open spiral strand with GALFAN-coating.</p> <p>As a pre-assembled cable system provided with a product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048</p> <p>System length (from pin center to pin center) [m]: XXX.XX</p> <p>Or equivalent.</p>
1.2	1,00 pc	<p>Pfeifer cable tension member type UMIX consisting of: 2 pcs. open swaged fitting type 620, 1 pc. open spiral strand with GALFAN coating. 1 pc. open spiral strand with GALFAN-coating.</p> <p>As a pre-assembled cable system provided with a product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048</p> <p>System length (from pin center to pin center) [m]: XXX.XX</p> <p>Or equivalent.</p>
1.3	1,00 pc	<p>Pfeifer cable tension member type UMIX consisting of: 2 pcs. swaged threaded rod fitting type 628, 1 pc. open spiral strand with GALFAN coating, 1 pc. open spiral strand with GALFAN-coating.</p> <p>As a pre-assembled cable system provided with a product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048</p> <p>System length (face thread to face thread) [m]: XXX,XX</p> <p>Or equivalent.</p>