

Threaded Fitting type 628




Material: structural grade carbon steel

Design: A set of nuts consisting of two nuts and one washer can be offered.

Installation: Please note installation manual!

Technical details: Dimensions without corrosion protection!

Length L after swaging



Size			008	010	012	014	016	020	024	027	030	036	042	048
Total length	L	mm	99	123	147	175	197	248	295	333	370	442	517	589
Total weight		kg	0.05	0.1	0.2	0.3	0.4	0.7	1.2	1.7	2.3	3.7	6.1	8.8
Tension Member														
Nomin. strand diameter	Ø D _c	mm	5.5	7	8.4	9.9	11.5	14.5	17.4	19.8	21.9	26.4	30.9	35.4
Fittings														
Corrosion protection: spray-galvanized, thread bright														
Material: structural grade carbon steel														
Diameter outer thread	Ø M _F	mm	8	10	12	14	16	20	24	27	30	36	42	48
Spanner flat width	SB _F	mm	2.5	4	5	6	7.5	10	11.5	12	12	16	18	21
Wrench size	SW _F	mm	9	11	12	15	17	23	27	30	34	39	47	52
Max. diameter swaged part	Ø D _{max}	mm	13	15	16	20	22	30	34	39	44	50	59	66
Length outer thread	Lg _{a,f}	mm	44	53.5	63	75.5	83	104.5	124	137.5	155	183.5	214	244