


Open Swaged Fitting type 620

new

Installation: Please note installation manual!

Technical details: Dimensions without corrosion protection!

Length L after swaging



Size			008	010	012	014	016	020	024	027	030	036	042	048
Total length	L	mm	97	120	148	174	198	245	295	334	366	442	515	583
Total weight		kg	0.13	0.23	0.4	0.7	1	2	3.1	4.5	6.2	10.2	15.4	22.4

Fork End

Corrosion protection: hot-dip galvanized

Material: According to ETA-18/0878

Dimension	A	mm	26	32	39	47	53	66	77	88	98	115	133	151
Dimension	B	mm	10	12	14	17	18	23	23.5	23.5	28.5	28.5	34	39
Dimension	C	mm	21	25.6	31	36	40	51	56.5	61.5	70.5	79.5	94	108
Dimension	E	mm	18.5	22.5	27.5	32	37	45	54	60	65	76	86	96
Dimension	F	mm	14.5	17.5	21.5	26	29	35	42	48	53	62	72	82
Dimension	H	mm	40.5	50	60.5	73	80	100	120	134	147	174	201	227

Pins

Corrosion protection: hot-dip galvanized / spray-galvanized

Material: According to ETA-18/0878

Pin length	G	mm	29	34.5	40.5	45.5	52	65	70.5	78	90	99	116	130
Pin diameter	ØD _p	mm	8	10	12	14	16	20	24	27	30	36	42	48

Connection Plate

Material: S355

Min. width	c _{min}	mm	27	33	40	48	54	66	84	105	106	145	166	187
Min. width quasi-static loads	c _{min}	mm	25	31	38	45	53	66	78	88	98	115	135	153
Plate thickness	t	mm	8	10	12	15	15	20	20	20	25	25	30	35
Diameter drilled hole	Ød _b	mm	9	11	13.5	16	18	22	26	30	33	39	45	51
Edge distance	f _{min}	mm	14.5	17.5	21.5	26	29	35	42	48	53	62	72	82

Fittings

Corrosion protection: spray-galvanized

Material: structural grade carbon steel

Max. diameter swaged part	ØD _{max}	mm	13	15	16	20	22	30	34	39	44	50	59	66
---------------------------	-------------------	----	----	----	----	----	----	----	----	----	----	----	----	----

Tension Member

Nomin. strand diameter	Ø D _c	mm	5.5	7	8.4	9.9	11.5	14.5	17.4	19.8	21.9	26.4	30.9	35.4
------------------------	------------------	----	-----	---	-----	-----	------	------	------	------	------	------	------	------