


Coupler UMIK - Stainless Steel



Material: Stainless steel

Installation: Please note installation manual!

Please note the minimum screw-in depth from the installation manual.



Size			008	010	012	014	016	020	024	027	030	036
Total weight	kg		0.03	0.1	0.1	0.2	0.2	0.5	0.8	1.1	1.6	2.2
Coupler												
Length	L_M	mm	56	68	80	104	92	129	153	171	196	232
Diameter inner thread	$\varnothing m_M$	mm	8	10	12	16	14	20	24	27	30	36
Outer diameter	$\varnothing D_M$	mm	12	15	18	24	21	30	36	40.5	45	54
Spanner flat width	SB_M	mm	12	12	12	16	12	16	16	16	20	20
Wrench size	SW_M	mm	11	13	16	22	19	27	32	36	40	49

Size			042	048	052	056	060	064	070	080	090	100
Total weight	kg		3.6	5.4	5.6	7.2	8.7	10.5	13.8	20.5	29.5	40
Coupler												
Length	L_M	mm	269	306	266	288	308	327	358	408	466	512
Diameter inner thread	$\varnothing m_M$	mm	42	48	52	56	60	64	70	80	90	100
Outer diameter	$\varnothing D_M$	mm	63	72	78	84	90	96	105	120	135	150
Spanner flat width	SB_M	mm	20	20	—	—	—	—	—	—	—	—
Wrench size	SW_M	mm	57	65	—	—	—	—	—	—	—	—