


Intersection Coupler UMX - Stainless Steel



Material: Stainless steel

Installation: Please note installation manual!

Please note the minimum screw-in depth from the installation manual.



Size			008	010	012	014	016	020	024	027	030	036
Total weight	kg		0.1	0.2	0.2	0.4	0.5	1	1.7	2.4	3.4	4.7
Intersection Coupler												
Length	L_K	mm	86	106	126	149	162	203	241	271	300	332
Diameter inner thread	$\varnothing m_K$	mm	8	10	12	14	16	20	24	27	30	36
Outer diameter	$\varnothing D_K$	mm	16	20	23	27	30	37	44	49	55	65
Width long hole	X_K	mm	10.5	13	15	17	19	23	27	30	34	40
Length long hole	Y_K	mm	26	31	36	41	48	57	67	78	84	100
Max. opening angle	a_K	°	125	125	125	125	125	125	125	125	125	125

Size			042	048	052	056	060	064	070	080	090	100
Total weight	kg		7.6	11.2	13.6	17.1	20.9	25.3	33.4	50	72.1	98.2
Intersection Coupler												
Length	L_K	mm	389	443	460	497	534	563	614	704	800	884
Diameter inner thread	$\varnothing m_K$	mm	42	48	52	56	60	64	70	80	90	100
Outer diameter	$\varnothing D_K$	mm	76	86	94	101	108	115	126	144	162	180
Width long hole	X_K	mm	46	52	57	61	65	69	76	86	96	106
Length long hole	Y_K	mm	117	133	146	159	172	177	192	222	250	278
Max. opening angle	a_K	°	125	125	125	125	125	125	125	125	125	125