

Product specification

1		Pfeifer Tension Rod System type UMIX
1.1	1,00 pc	<p>Pfeifer tension rod system type UMIX, galvanized, consisting of: 1 pc. fork end RHT, incl. pin and lock nut RHT, 1 pc. fork end LHT, incl. pin and lock nut LHT, 1 pc. tension rod with hot-dip galvanized thread on both sides.</p> <p>Fabricated according to European Technical Assessment ETA-18/0878 as pre-assembled tension rod system with product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100 / 110 / 120</p> <p>System length (from pin center to pin center) [m]: XXX,XX</p> <p>Or equivalent.</p>
1.2	1,00 pc	<p>Pfeifer tension rod system type UMIX, galvanized with adapter consisting of: 2 pc. fork end RHT, incl. pin and lock nut RHT, 1 pc. adapter RHT/LHT, 1 pc. tension rod with hot-dip galvanized thread on both sides</p> <p>Fabricated according to European Technical Assessment ETA-18/0878 as pre-assembled tension rod system with product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100 / 110 / 120</p> <p>System length (from pin center to pin center) [m]: XXX,XX</p> <p>Or equivalent.</p>
1.3	1,00 pc	<p>Pfeifer tension rod system type UMIX, galvanized with coupler/intersection coupler/connector consisting of: 1 pc. fork end RHT, incl. pin and lock nut RHY, 1 pc. fork end LHT incl. pin and lock nut LHT, 1 pc. Coupler, incl. lock nuts RHY/LHT/intersection coupler incl. lock nuts RHT/LH T/connector, 2 pcs. tension rod with hot-dip galvanized thread on both sides</p> <p>Fabricated according to European Technical Assessment ETA-18/0878 as partially pre-assembled (split at coupler/connector) and provided with product-specific label.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100 / 110 / 120</p> <p>System length (from pin center to pin center) [m]: XXX,XX</p> <p>Joint position (pin center to center of coupler)/connector position (pin center to center of connector) [m]: XXX,XX</p> <p>Or equivalent.</p>
1.4	1,00 pc	<p>Pfeifer tension rod systems type UMIX, galvanized with intersection plate consisting of: 4 pcs. fork end RHT, incl. pin and lock nut RHT, 4 pcs. fork end LHT, incl. pin and lock nut LHT, 1 pc. intersection plate, 4 pcs. tension rod with hot-dip galvanized thread on both sides.</p> <p>Fabricated according to European Technical Assessment ETA-18/0878 as pre-assembled tension rod systems provided with product-specific labels.</p> <p>System size: 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100 / 110 / 120</p> <p>System diagonal (pin center to pin center) [m]: XXX,XX</p> <p>Opening angle (40–90°) [°]: XX</p> <p>Or equivalent.</p>